West Virginia Department of Environmental Protection Division of Air Quality

Jim Justice Governor Austin Caperton Cabinet Secretary

Permit to Operate



Pursuant to **Title V**of the Clean Air Act

Issued to:

Cranberry Pipeline Corporation Horsemill Compressor Station R30-03900075-2017

> uam F. Durn Director

Issued: September 7, 2017 • Effective: September 21, 2017
Expiration: September 7, 2022 • Renewal Application Due: March 7, 2022

Permit Number: R30-03900075-2017
Permittee: Cranberry Pipeline Corporation
Facility Name: Horsemill Compressor Station

Permittee Mailing Address: 900 Lee Street East, Suite 1500, Charleston, WV 25301

This permit is issued in accordance with the West Virginia Air Pollution Control Act (West Virginia Code §§ 22-5-1 et seq.) and 45CSR30 — Requirements for Operating Permits. The permittee identified at the above-referenced facility is authorized to operate the stationary sources of air pollutants identified herein in accordance with all terms and conditions of this permit.

Facility Location:

Cedar Grove, Kanawha County, West Virginia

Facility Mailing Address:

Same as above

Telephone Number:

(304) 347-1642

Type of Business Entity:

Corporation

Facility Description:

Natural Gas Gathering Facility

SIC Codes:

Primary 1311; Secondary NA; Tertiary NA

UTM Coordinates:

461.62 km Easting • 4232.35 km Northing • Zone 17

Permit Writer: Frederick Tipane

Any person whose interest may be affected, including, but not necessarily limited to, the applicant and any person who participated in the public comment process, by a permit issued, modified or denied by the Secretary may appeal such action of the Secretary to the Air Quality Board pursuant to article one [§§ 22B-1-1 et seq.], Chapter 22B of the Code of West Virginia. West Virginia Code §22-5-14.

Issuance of this Title V Operating Permit does not supersede or invalidate any existing permits under 45CSR13, 14 or 19, although all applicable requirements from such permits governing the facility's operation and compliance have been incorporated into the Title V Operating Permit.

Table of Contents

1.0	Emission Units and Active R13, R14, and R19 Permits	3
2.0	General Conditions	4
3.0	Facility-Wide Requirements	13
	Source-specific Requirements	
4.0	Dehydration and Reboiler	21
5.0	Exemption (Less than 1 ton/year Benzene Exemption Subpart HH)	24
6.0	Compressor Engines #1 and #2	27

1.0 Emission Units and Active R13, R14, and R19 Permits

1.1. Emission Units

Emission Unit ID	Emission Point ID	Emission Unit Description	Year Installed	Design Capacity	Control Device
#1	001-02	Reciprocating Engine/Integral Compressor; White Superior 6GT825; Serial # 274469 (4SRB)	1983	600 HP	N/A
#2	001-03	Reciprocating Engine/Integral Compressor; White Superior 80-825; Serial # 20812 (4SRB)	1985	800 HP	N/A
RBV-1	001-04	NATCO Model 90-200 Glycol Dehydration Unit Reboiler Vent	2009	0.25 mmBtu/hr	N/A
RSV-1	001-05	NATCO Model 90-200 Glycol Dehydration Unit Regenerator Still Vent	2009	30 mmscf/day	N/A
005	001-06	Used Engine Oil Storage Tank	1986	1050 Gallons	N/A
006	001-07	New Engine Oil Storage Tank	1986	2000 Gallons	N/A
007	001-08	Pipeline Fluids Storage Tank	1986	1050 Gallons	N/A

1.2. Active R13, R14, and R19 Permits

The underlying authority for any conditions from R13, R14, and/or R19 permits contained in this operating permit is cited using the original permit number (e.g. R13-1234). The current applicable version of such permit(s) is listed below.

Permit Number	Date of Issuance	
R13-2808B	May 10, 2013	

2.0 General Conditions

2.1. Definitions

- 2.1.1. All references to the "West Virginia Air Pollution Control Act" or the "Air Pollution Control Act" mean those provisions contained in W.Va. Code §§ 22-5-1 to 22-5-18.
- 2.1.2. The "Clean Air Act" means those provisions contained in 42 U.S.C. §§ 7401 to 7671q, and regulations promulgated thereunder.
- 2.1.3. "Secretary" means the Secretary of the Department of Environmental Protection or such other person to whom the Secretary has delegated authority or duties pursuant to W.Va. Code §§ 22-1-6 or 22-1-8 (45CSR§30-2.12.). The Director of the Division of Air Quality is the Secretary's designated representative for the purposes of this permit.
- 2.1.4. Unless otherwise specified in a permit condition or underlying rule or regulation, all references to a "rolling yearly total" shall mean the sum of the monthly data, values or parameters being measured, monitored, or recorded, at any given time for the previous twelve (12) consecutive calendar months.

2.2. Acronyms

CAAA	Clean Air Act Amendments	NSPS	New Source Performance
CBI	Confidential Business Information		Standards
CEM	Continuous Emission Monitor	PM	Particulate Matter
CES	Certified Emission Statement	PM_{10}	Particulate Matter less than
C.F.R. or CFR	Code of Federal Regulations		10μm in diameter
CO	Carbon Monoxide	pph	Pounds per Hour
C.S.R. or CSR	Codes of State Rules	ppm	Parts per Million
DAQ	Division of Air Quality	PSD	Prevention of Significant
DEP	Department of Environmental		Deterioration
	Protection	psi	Pounds per Square Inch
FOIA	Freedom of Information Act	SIC	Standard Industrial
HAP	Hazardous Air Pollutant		Classification
HON	Hazardous Organic NESHAP	SIP	State Implementation Plan
HP	Horsepower	SO ₂	Sulfur Dioxide
lbs/hr <i>or</i> lb/hr	Pounds per Hour	TAP	Toxic Air Pollutant
LDAR	Leak Detection and Repair	TPY	Tons per Year
m	Thousand	TRS	Total Reduced Sulfur
MACT	Maximum Achievable Control	TSP	Total Suspended Particulate
	Technology	USEPA	United States
mm	Million		Environmental Protection
mmBtu/hr	Million British Thermal Units per		Agency
	Hour	UTM	Universal Transverse
mmft³/hr <i>or</i>	Million Cubic Feet Burned per		Mercator
mmcf/hr	Hour	VEE	Visual Emissions
NA or N/A	Not Applicable		Evaluation
NAAQS	National Ambient Air Quality	VOC	Volatile Organic
	Standards		Compounds
NESHAPS	National Emissions Standards for		1
	Hazardous Air Pollutants		
NO _x	Nitrogen Oxides		

2.3. Permit Expiration and Renewal

- 2.3.1. Permit duration. This permit is issued for a fixed term of five (5) years and shall expire on the date specified on the cover of this permit, except as provided in 45CSR§30-6.3.b. and 45CSR§30-6.3.c. [45CSR§30-5.1.b.]
- 2.3.2. A permit renewal application is timely if it is submitted at least six (6) months prior to the date of permit expiration.

[45CSR§30-4.1.a.3.]

- 2.3.3. Permit expiration terminates the source's right to operate unless a timely and complete renewal application has been submitted consistent with 45CSR§30-6.2. and 45CSR§30-4.1.a.3.

 [45CSR§30-6.3.b.]
- 2.3.4. If the Secretary fails to take final action to deny or approve a timely and complete permit application before the end of the term of the previous permit, the permit shall not expire until the renewal permit has been issued or denied, and any permit shield granted for the permit shall continue in effect during that time.

 [45CSR§30-6.3.c.]

2.4. Permit Actions

2.4.1. This permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any permit condition.

[45CSR§30-5.1.f.3.]

2.5. Reopening for Cause

- 2.5.1. This permit shall be reopened and revised under any of the following circumstances:
 - a. Additional applicable requirements under the Clean Air Act or the Secretary's legislative rules become applicable to a major source with a remaining permit term of three (3) or more years. Such a reopening shall be completed not later than eighteen (18) months after promulgation of the applicable requirement. No such reopening is required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions has been extended pursuant to 45CSR§§30-6.6.a.1.A. or B.
 - b. Additional requirements (including excess emissions requirements) become applicable to an affected source under Title IV of the Clean Air Act (Acid Deposition Control) or other legislative rules of the Secretary. Upon approval by U.S. EPA, excess emissions offset plans shall be incorporated into the permit.
 - c. The Secretary or U.S. EPA determines that the permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of the permit.
 - d. The Secretary or U.S. EPA determines that the permit must be revised or revoked and reissued to assure compliance with the applicable requirements.

[45CSR§30-6.6.a.]

2.6. Administrative Permit Amendments

2.6.1. The permittee may request an administrative permit amendment as defined in and according to the procedures specified in 45CSR§30-6.4.

[45CSR§30-6.4.]

2.7. Minor Permit Modifications

2.7.1. The permittee may request a minor permit modification as defined in and according to the procedures specified in 45CSR§30-6.5.a.

[45CSR§30-6.5.a.]

2.8. Significant Permit Modification

2.8.1. The permittee may request a significant permit modification, in accordance with 45CSR§30-6.5.b., for permit modifications that do not qualify for minor permit modifications or as administrative amendments.

[45CSR§30-6.5.b.]

2.9. Emissions Trading

2.9.1. No permit revision shall be required, under any approved economic incentives, marketable permits, emissions trading, and other similar programs or processes for changes that are provided for in the permit and that are in accordance with all applicable requirements.

[45CSR§30-5.1.h.]

2.10. Off-Permit Changes

- 2.10.1. Except as provided below, a facility may make any change in its operations or emissions that is not addressed nor prohibited in its permit and which is not considered to be construction nor modification under any rule promulgated by the Secretary without obtaining an amendment or modification of its permit. Such changes shall be subject to the following requirements and restrictions:
 - a. The change must meet all applicable requirements and may not violate any existing permit term or condition.
 - b. The permittee must provide a written notice of the change to the Secretary and to U.S. EPA within two (2) business days following the date of the change. Such written notice shall describe each such change, including the date, any change in emissions, pollutants emitted, and any applicable requirement that would apply as a result of the change.
 - c. The change shall not qualify for the permit shield.
 - d. The permittee shall keep records describing all changes made at the source that result in emissions of regulated air pollutants, but not otherwise regulated under the permit, and the emissions resulting from those changes.
 - e. No permittee may make any change subject to any requirement under Title IV of the Clean Air Act (Acid Deposition Control) pursuant to the provisions of 45CSR§30-5.9.

f. No permittee may make any changes which would require preconstruction review under any provision of Title I of the Clean Air Act (including 45CSR14 and 45CSR19) pursuant to the provisions of 45CSR\$30-5.9.

[45CSR§30-5.9.]

2.11. Operational Flexibility

2.11.1. The permittee may make changes within the facility as provided by § 502(b)(10) of the Clean Air Act. Such operational flexibility shall be provided in the permit in conformance with the permit application and applicable requirements. No such changes shall be a modification under any rule or any provision of Title I of the Clean Air Act (including 45CSR14 and 45CSR19) promulgated by the Secretary in accordance with Title I of the Clean Air Act and the change shall not result in a level of emissions exceeding the emissions allowable under the permit.

[45CSR§30-5.8]

2.11.2. Before making a change under 45CSR§30-5.8., the permittee shall provide advance written notice to the Secretary and to U.S. EPA, describing the change to be made, the date on which the change will occur, any changes in emissions, and any permit terms and conditions that are affected. The permittee shall thereafter maintain a copy of the notice with the permit, and the Secretary shall place a copy with the permit in the public file. The written notice shall be provided to the Secretary and U.S. EPA at least seven (7) days prior to the date that the change is to be made, except that this period may be shortened or eliminated as necessary for a change that must be implemented more quickly to address unanticipated conditions posing a significant health, safety, or environmental hazard. If less than seven (7) days notice is provided because of a need to respond more quickly to such unanticipated conditions, the permittee shall provide notice to the Secretary and U.S. EPA as soon as possible after learning of the need to make the change.

[45CSR§30-5.8.a.]

- 2.11.3. The permit shield shall not apply to changes made under 45CSR§30-5.8., except those provided for in 45CSR§30-5.8.d. However, the protection of the permit shield will continue to apply to operations and emissions that are not affected by the change, provided that the permittee complies with the terms and conditions of the permit applicable to such operations and emissions. The permit shield may be reinstated for emissions and operations affected by the change:
 - a. If subsequent changes cause the facility's operations and emissions to revert to those authorized in the permit and the permittee resumes compliance with the terms and conditions of the permit, or
 - b. If the permittee obtains final approval of a significant modification to the permit to incorporate the change in the permit.

[45CSR§30-5.8.c.]

2.11.4. "Section 502(b)(10) changes" are changes that contravene an express permit term. Such changes do not include changes that would violate applicable requirements or contravene enforceable permit terms and conditions that are monitoring (including test methods), recordkeeping, reporting, or compliance certification requirements.

[45CSR§30-2.39]

2.12. Reasonably Anticipated Operating Scenarios

- 2.12.1. The following are terms and conditions for reasonably anticipated operating scenarios identified in this permit.
 - a. Contemporaneously with making a change from one operating scenario to another, the permittee shall record in a log at the permitted facility a record of the scenario under which it is operating and to document the change in reports submitted pursuant to the terms of this permit and 45CSR30.
 - b. The permit shield shall extend to all terms and conditions under each such operating scenario; and
 - c. The terms and conditions of each such alternative scenario shall meet all applicable requirements and the requirements of 45CSR30.

[45CSR§30-5.1.i.]

2.13. Duty to Comply

2.13.1. The permittee must comply with all conditions of this permit. Any permit noncompliance constitutes a violation of the West Virginia Code and the Clean Air Act and is grounds for enforcement action by the Secretary or USEPA; for permit termination, revocation and reissuance, or modification; or for denial of a permit renewal application.

[45CSR§30-5.1.f.1.]

2.14. Inspection and Entry

- 2.14.1. The permittee shall allow any authorized representative of the Secretary, upon the presentation of credentials and other documents as may be required by law, to perform the following:
 - a. At all reasonable times (including all times in which the facility is in operation) enter upon the permittee's premises where a source is located or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
 - b. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
 - c. Inspect at reasonable times (including all times in which the facility is in operation) any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit;
 - d. Sample or monitor at reasonable times substances or parameters to determine compliance with the permit or applicable requirements or ascertain the amounts and types of air pollutants discharged.

[45CSR§30-5.3.b.]

2.15. Schedule of Compliance

- 2.15.1. For sources subject to a compliance schedule, certified progress reports shall be submitted consistent with the applicable schedule of compliance set forth in this permit and 45CSR§30-4.3.h., but at least every six (6) months, and no greater than once a month, and shall include the following:
 - Dates for achieving the activities, milestones, or compliance required in the schedule of compliance, and dates when such activities, milestones or compliance were achieved; and
 - b. An explanation of why any dates in the schedule of compliance were not or will not be met, and any preventative or corrective measure adopted.

[45CSR§30-5.3.d.]

2.16. Need to Halt or Reduce Activity not a Defense

2.16.1. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. However, nothing in this paragraph shall be construed as precluding consideration of a need to halt or reduce activity as a mitigating factor in determining penalties for noncompliance if the health, safety, or environmental impacts of halting or reducing operations would be more serious than the impacts of continued operations. [45CSR§30-5.1.f.2.]

2.17. Emergency

- 2.17.1. An "emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the source, including acts of God, which situation requires immediate corrective action to restore normal operation, and that causes the source to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include noncompliance to the extent caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.
- 2.17.2. Effect of any emergency. An emergency constitutes an affirmative defense to an action brought for noncompliance with such technology-based emission limitations if the conditions of 45CSR§30-5.7.c. are met.

[45CSR§30-5.7.b.]

[45CSR§30-5.7.a.]

- 2.17.3. The affirmative defense of emergency shall be demonstrated through properly signed, contemporaneous operating logs, or other relevant evidence that:
 - a. An emergency occurred and that the permittee can identify the cause(s) of the emergency;
 - b. The permitted facility was at the time being properly operated;
 - c. During the period of the emergency the permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards, or other requirements in the permit; and

d. Subject to the requirements of 45CSR§30-5.1.c.3.C.1, the permittee submitted notice of the emergency to the Secretary within one (1) working day of the time when emission limitations were exceeded due to the emergency and made a request for variance, and as applicable rules provide. This notice, report, and variance request fulfills the requirement of 45CSR§30-5.1.c.3.B. This notice must contain a detailed description of the emergency, any steps taken to mitigate emissions, and corrective actions taken.

[45CSR§30-5.7.c.]

2.17.4. In any enforcement proceeding, the permittee seeking to establish the occurrence of an emergency has the burden of proof.

[45CSR§30-5.7.d.]

2.17.5. This provision is in addition to any emergency or upset provision contained in any applicable requirement. [45CSR§30-5.7.e.]

2.18. Federally-Enforceable Requirements

- 2.18.1. All terms and conditions in this permit, including any provisions designed to limit a source's potential to emit and excepting those provisions that are specifically designated in the permit as "State-enforceable only", are enforceable by the Secretary, USEPA, and citizens under the Clean Air Act.
 [45CSR§30-5.2.a.]
- 2.18.2. Those provisions specifically designated in the permit as "State-enforceable only" shall become "Federally-enforceable" requirements upon SIP approval by the USEPA.

2.19. Duty to Provide Information

2.19.1. The permittee shall furnish to the Secretary within a reasonable time any information the Secretary may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the Secretary copies of records required to be kept by the permittee. For information claimed to be confidential, the permittee shall furnish such records to the Secretary along with a claim of confidentiality in accordance with 45CSR31. If confidential information is to be sent to USEPA, the permittee shall directly provide such information to USEPA along with a claim of confidentiality in accordance with 40 C.F.R. Part 2. [45CSR§30-5.1.f.5.]

2.20. Duty to Supplement and Correct Information

2.20.1. Upon becoming aware of a failure to submit any relevant facts or a submittal of incorrect information in any permit application, the permittee shall promptly submit to the Secretary such supplemental facts or corrected information.

[45CSR§30-4.2.]

2.21. Permit Shield

- 2.21.1. Compliance with the conditions of this permit shall be deemed compliance with any applicable requirements as of the date of permit issuance provided that such applicable requirements are included and are specifically identified in this permit or the Secretary has determined that other requirements specifically identified are not applicable to the source and this permit includes such a determination or a concise summary thereof. [45CSR§30-5.6.a.]
- 2.21.2. Nothing in this permit shall alter or affect the following:
 - a. The liability of an owner or operator of a source for any violation of applicable requirements prior to or at the time of permit issuance; or
 - b. The applicable requirements of the Code of West Virginia and Title IV of the Clean Air Act (Acid Deposition Control), consistent with § 408 (a) of the Clean Air Act.
 - c. The authority of the Administrator of U.S. EPA to require information under § 114 of the Clean Air Act or to issue emergency orders under § 303 of the Clean Air Act.

[45CSR§30-5.6.c.]

2.22. Credible Evidence

2.22.1. Nothing in this permit shall alter or affect the ability of any person to establish compliance with, or a violation of, any applicable requirement through the use of credible evidence to the extent authorized by law. Nothing in this permit shall be construed to waive any defenses otherwise available to the permittee including but not limited to any challenge to the credible evidence rule in the context of any future proceeding.
[45CSR§30-5.3.e.3.B. and 45CSR38]

2.23. Severability

2.23.1. The provisions of this permit are severable. If any provision of this permit, or the application of any provision of this permit to any circumstance is held invalid by a court of competent jurisdiction, the remaining permit terms and conditions or their application to other circumstances shall remain in full force and effect.

[45CSR§30-5.1.e.]

2.24. Property Rights

2.24.1. This permit does not convey any property rights of any sort or any exclusive privilege. [45CSR§30-5.1.f.4]

2.25. Acid Deposition Control

- 2.25.1. Emissions shall not exceed any allowances that the source lawfully holds under Title IV of the Clean Air Act (Acid Deposition Control) or rules of the Secretary promulgated thereunder.
 - a. No permit revision shall be required for increases in emissions that are authorized by allowances acquired pursuant to the acid deposition control program, provided that such increases do not require a permit revision under any other applicable requirement.

- b. No limit shall be placed on the number of allowances held by the source. The source may not, however, use allowances as a defense to noncompliance with any other applicable requirement.
- c. Any such allowance shall be accounted for according to the procedures established in rules promulgated under Title IV of the Clean Air Act.

[45CSR§30-5.1.d.]

2.25.2. Where applicable requirements of the Clean Air Act are more stringent than any applicable requirement of regulations promulgated under Title IV of the Clean Air Act (Acid Deposition Control), both provisions shall be incorporated into the permit and shall be enforceable by the Secretary and U. S. EPA.

[45CSR§30-5.1.a.2.]

3.0 Facility-Wide Requirements

3.1. Limitations and Standards

- 3.1.1. Open burning. The open burning of refuse by any person is prohibited except as noted in 45CSR§6-3.1. [45CSR§6-3.1.]
- 3.1.2. **Open burning exemptions.** The exemptions listed in 45CSR§6-3.1 are subject to the following stipulation: Upon notification by the Secretary, no person shall cause or allow any form of open burning during existing or predicted periods of atmospheric stagnation. Notification shall be made by such means as the Secretary may deem necessary and feasible.

 [45CSR§6-3.2.]
- 3.1.3. Asbestos. The permittee is responsible for thoroughly inspecting the facility, or part of the facility, prior to commencement of demolition or renovation for the presence of asbestos and complying with 40 C.F.R. §61.145, 40 C.F.R. §61.148, and 40 C.F.R. §61.150. The permittee, owner, or operator must notify the Secretary at least ten (10) working days prior to the commencement of any asbestos removal on the forms prescribed by the Secretary if the permittee is subject to the notification requirements of 40 C.F.R. §61.145(b)(3)(i). The USEPA, the Division of Waste Management and the Bureau for Public Health Environmental Health require a copy of this notice to be sent to them.

 [40 C.F.R. §61.145(b) and 45CSR34]
- 3.1.4. Odor. No person shall cause, suffer, allow or permit the discharge of air pollutants which cause or contribute to an objectionable odor at any location occupied by the public.
 [45CSR§4-3.1 State-Enforceable only.]
- 3.1.5. Standby plan for reducing emissions. When requested by the Secretary, the permittee shall prepare standby plans for reducing the emissions of air pollutants in accordance with the objectives set forth in Tables I, II, and III of 45CSR11.

 [45CSR\$11-5.2]
- 3.1.6. Emission inventory. The permittee is responsible for submitting, on an annual basis, an emission inventory in accordance with the submittal requirements of the Division of Air Quality.

 [W.Va. Code § 22-5-4(a)(14)]
- 3.1.7. **Ozone-depleting substances.** For those facilities performing maintenance, service, repair or disposal of appliances, the permittee shall comply with the standards for recycling and emissions reduction pursuant to 40 C.F.R. Part 82, Subpart F, except as provided for Motor Vehicle Air Conditioners (MVACs) in Subpart B:
 - a. Persons opening appliances for maintenance, service, repair, or disposal must comply with the prohibitions and required practices pursuant to 40 C.F.R. §§82.154 and 82.156.
 - b. Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 C.F.R. §82.158.

c. Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 C.F.R. §82.161.

[40 C.F.R. 82, Subpart F]

- 3.1.8. Risk Management Plan. Should this stationary source, as defined in 40 C.F.R. §68.3, become subject to Part 68, then the owner or operator shall submit a risk management plan (RMP) by the date specified in 40 C.F.R. §68.10 and shall certify compliance with the requirements of Part 68 as part of the annual compliance certification as required by 40 C.F.R. Part 70 or 71.

 [40 C.F.R. 68]
- 3.1.9. No person shall cause, suffer, allow or permit fugitive particulate matter to be discharged beyond the boundary lines of the property on which the discharge originates or at any public or residential location, which causes or contributes to statutory air pollution.

 [45CSR§17-3.1; State Enforceable Only]
- 3.1.10. Minor Source of Hazardous Air Pollutants (HAP). HAP emissions from the affected facility shall be less than 10 tons/year of any single HAP or 25 tons/year of any combination of HAPs. Compliance with this Section shall ensure that the affected facility is a minor HAP source.

 [45CSR13, R13-2808, 4.1.2.]

3.2. Monitoring Requirements

3.2.1. Reserved

3.3. Testing Requirements

- 3.3.1. Stack testing. As per provisions set forth in this permit or as otherwise required by the Secretary, in accordance with the West Virginia Code, underlying regulations, permits and orders, the permittee shall conduct test(s) to determine compliance with the emission limitations set forth in this permit and/or established or set forth in underlying documents. The Secretary, or his duly authorized representative, may at his option witness or conduct such test(s). Should the Secretary exercise his option to conduct such test(s), the operator shall provide all necessary sampling connections and sampling ports to be located in such manner as the Secretary may require, power for test equipment and the required safety equipment, such as scaffolding, railings and ladders, to comply with generally accepted good safety practices. Such tests shall be conducted in accordance with the methods and procedures set forth in this permit or as otherwise approved or specified by the Secretary in accordance with the following:
 - a. The Secretary may on a source-specific basis approve or specify additional testing or alternative testing to the test methods specified in the permit for demonstrating compliance with 40 C.F.R. Parts 60, 61, and 63, if applicable, in accordance with the Secretary's delegated authority and any established equivalency determination methods which are applicable.
 - b. The Secretary may on a source-specific basis approve or specify additional testing or alternative testing to the test methods specified in the permit for demonstrating compliance with applicable requirements which do not involve federal delegation. In specifying or approving such alternative testing to the test methods, the Secretary, to the extent possible, shall utilize the same equivalency criteria as would be used in approving such changes under Section 3.3.1.a. of this permit.

- c. All periodic tests to determine mass emission limits from or air pollutant concentrations in discharge stacks and such other tests as specified in this permit shall be conducted in accordance with an approved test protocol. Unless previously approved, such protocols shall be submitted to the Secretary in writing at least thirty (30) days prior to any testing and shall contain the information set forth by the Secretary. In addition, the permittee shall notify the Secretary at least fifteen (15) days prior to any testing so the Secretary may have the opportunity to observe such tests. This notification shall include the actual date and time during which the test will be conducted and, if appropriate, verification that the tests will fully conform to a referenced protocol previously approved by the Secretary.
- d. The permittee shall submit a report of the results of the stack test within 60 days of completion of the test. The test report shall provide the information necessary to document the objectives of the test and to determine whether proper procedures were used to accomplish these objectives. The report shall include the following: the certification described in paragraph 3.5.1; a statement of compliance status, also signed by a responsible official; and, a summary of conditions which form the basis for the compliance status evaluation. The summary of conditions shall include the following:
 - 1. The permit or rule evaluated, with the citation number and language.
 - 2. The result of the test for each permit or rule condition.
 - 3. A statement of compliance or non-compliance with each permit or rule condition.

[WV Code §§ 22-5-4(a)(14-15) and 45CSR13]

3.4. Recordkeeping Requirements

- 3.4.1. **Monitoring information.** The permittee shall keep records of monitoring information that include the following:
 - a. The date, place as defined in this permit and time of sampling or measurements;
 - b. The date(s) analyses were performed;
 - c. The company or entity that performed the analyses;
 - d. The analytical techniques or methods used;
 - e. The results of the analyses; and
 - f. The operating conditions existing at the time of sampling or measurement.

[45CSR§30-5.1.c.2.A., 45CSR13, R13-2808, 4.2.1.]

3.4.2. **Retention of records.** The permittee shall maintain and retain records of all required information (including monitoring data, support information, reports and notifications) required by this permit for a period of at least five (5) years from the date of each occurrence, monitoring sample, measurement, maintenance, corrective action, report, application, or record creation date. Such records shall be recorded in a form suitable and readily available for expeditious inspection and review. Support information includes all calibration and

maintenance records and all original strip-chart recordings for continuous monitoring instrumentation and copies of all reports required by the permit.

- a. For records required by Permit R13-2808 (RBV-1 and RSV-1), at a minimum, the most recent two (2) years of data shall be maintained on site. The remaining three (3) years of data may be maintained off site, but must remain accessible within a reasonable time.
- b. For records required by 40 CFR 63 Subpart ZZZZ (Engines #1 and #2), at a minimum, the most recent two (2) years of data shall be retained on site. The remaining three (3) years of data may be retained off site.

Where appropriate, the permittee may maintain records in computerized form (e.g., on a computer, on computer floppy disks, CDs, DVDs, or magnetic tape disks), on microfilm, or on microfiche. [45CSR§30-5.1.c.2.B., 45CSR13, R13-2808, 3.4.1., 45CSR34, 40 CFR §63.10(b)(1)]

- 3.4.3. Odors. For the purposes of 45CSR4, the permittee shall maintain a record of all odor complaints received, any investigation performed in response to such a complaint, and any responsive action(s) taken.

 [45CSR§30-5.1.c. State-Enforceable only.]
- 3.4.4. The permittee shall maintain records of annual HAP emissions using AP-42 emission factors, GRI-GLYCalc model outputs, manufacturer guaranteed values, sample and/or test data, or other methods approved by DAQ demonstrating that facility-wide emissions are less than those specified in Section 3.1.10.

 [45CSR13, R13-2808, 4.2.4.]

3.5. Reporting Requirements

- 3.5.1. **Responsible official.** Any application form, report, or compliance certification required by this permit to be submitted to the DAQ and/or USEPA shall contain a certification by the responsible official that states that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate and complete.

 [45CSR§§30-4.4. and 5.1.c.3.D.]
- 3.5.2. A permittee may request confidential treatment for the submission of reporting required under 45CSR§30-5.1.c.3. pursuant to the limitations and procedures of W.Va. Code § 22-5-10 and 45CSR31. [45CSR§30-5.1.c.3.E.]
- 3.5.3. Except for the electronic submittal of the annual compliance certification and semi-annual monitoring reports to the DAQ and USEPA as required in 3.5.5 and 3.5.6 below, all notices, requests, demands, submissions and other communications required or permitted to be made to the Secretary of DEP and/or USEPA shall be made in writing and shall be deemed to have been duly given when delivered by hand, or mailed first class or by private carrier with postage prepaid to the address(es), or submitted in electronic format by e-mail as set forth below or to such other person or address as the Secretary of the Department of Environmental Protection may designate:

DAQ:

US EPA:

Director WVDEP

Associate Director

Division of Air Quality 601 57th Street SE Charleston, WV 25304

Office of Air Enforcement and Compliance Assistance (3AP20) U. S. Environmental Protection Agency Region III 1650 Arch Street

Philadelphia, PA 19103-2029

DAQ Compliance and Enforcement¹:

DEPAirQualityReports@wv.gov

¹For all self-monitoring reports (MACT, GACT, NSPS, etc.), stack tests and protocols, Notice of Compliance Status reports, Initial Notifications, etc.

- 3.5.4. Certified emissions statement. The permittee shall submit a certified emissions statement and pay fees on an annual basis in accordance with the submittal requirements of the Division of Air Quality.

 [45CSR§30-8.]
- 3.5.5. Compliance certification. The permittee shall certify compliance with the conditions of this permit on the forms provided by the DAQ. In addition to the annual compliance certification, the permittee may be required to submit certifications more frequently under an applicable requirement of this permit. The annual certification shall be submitted to the DAQ and USEPA on or before March 15 of each year, and shall certify compliance for the period ending December 31. The permittee shall maintain a copy of the certification on site for five (5) years from submittal of the certification. The annual certification shall be submitted in electronic format by e-mail to the following addresses:

DAQ: US EPA:

DEPAirQualityReports@wv.gov R3_APD_Permits@epa.gov

[45CSR§30-5.3.e.]

3.5.6. Semi-annual monitoring reports. The permittee shall submit reports of any required monitoring on or before September 15 for the reporting period January 1 to June 30 and on or before March 15 for the reporting period July 1 to December 31. All instances of deviation from permit requirements must be clearly identified in such reports. All required reports must be certified by a responsible official consistent with 45CSR§30-4.4. The semi-annual monitoring reports shall be submitted in electronic format by e-mail to the following address:

DAO:

DEPAirQualityReports@wv.gov

[45CSR§30-5.1.c.3.A.]

- 3.5.7. Emergencies. For reporting emergency situations, refer to Section 2.17 of this permit.
- 3.5.8. Deviations.
 - a. In addition to monitoring reports required by this permit, the permittee shall promptly submit supplemental reports and notices in accordance with the following:

- 1. Any deviation resulting from an emergency or upset condition, as defined in 45CSR§30-5.7., shall be reported by telephone or telefax within one (1) working day of the date on which the permittee becomes aware of the deviation, if the permittee desires to assert the affirmative defense in accordance with 45CSR§30-5.7. A written report of such deviation, which shall include the probable cause of such deviations, and any corrective actions or preventative measures taken, shall be submitted and certified by a responsible official within ten (10) days of the deviation.
- 2. Any deviation that poses an imminent and substantial danger to public health, safety, or the environment shall be reported to the Secretary immediately by telephone or telefax. A written report of such deviation, which shall include the probable cause of such deviation, and any corrective actions or preventative measures taken, shall be submitted by the responsible official within ten (10) days of the deviation.
- 3. Deviations for which more frequent reporting is required under this permit shall be reported on the more frequent basis.
- 4. All reports of deviations shall identify the probable cause of the deviation and any corrective actions or preventative measures taken.

[45CSR§30-5.1.c.3.C.]

- b. The permittee shall, in the reporting of deviations from permit requirements, including those attributable to upset conditions as defined in this permit, report the probable cause of such deviations and any corrective actions or preventive measures taken in accordance with any rules of the Secretary.

 [45CSR§30-5.1.c.3.B.]
- 3.5.9. New applicable requirements. If any applicable requirement is promulgated during the term of this permit, the permittee will meet such requirements on a timely basis, or in accordance with a more detailed schedule if required by the applicable requirement.

 [45CSR§30-4.3.h.1.B.]

3.6. Compliance Plan

3.6.1. Reserved

3.7. Permit Shield

- 3.7.1. The permittee is hereby granted a permit shield in accordance with 45CSR§30-5.6. The permit shield applies provided the permittee operates in accordance with the information contained within this permit.
- 3.7.2. The following requirements specifically identified are not applicable to the source based on the determinations set forth below. The permit shield shall apply to the following requirements provided the conditions of the determinations are met.
 - **45CSR10** *To Prevent and Control Air Pollution from the Emission of Sulfur Oxides:* 45CSR10 is not applicable to the facility's reboiler because its maximum design heat input (DHI) is less than 10 MMBtu/hr.

- 45CSR21 Regulation To Prevent and Control Air Pollution from the Emission of Volatile Organic Compounds: The storage tanks at the station, are below 40,000 gallons in capacity and therefore not subject to 45CSR§21-28 per 45CSR§21-28.1.a.. The compressor station is not engaged in the extraction or fractionation of natural gas and therefore is not defined as a "Natural gas processing plant" per 45CSR§21-29.2.h., hence it is not subject to 45CSR§21-29.
- 45CSR27 To Prevent and Control the Emissions of Toxic Air Pollutants: Natural gas is included as a petroleum product and contains less than 5% benzene by weight. 45CSR§27-2.4 exempts equipment "used in the production and distribution of petroleum products providing that such equipment does not produce or contact materials containing more than 5% benzene by weight."
- 40 CFR 60 Subpart Dc Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units: The reboiler is less than 10 mmBtu/hr. Therefore; Subpart Dc is not applicable in accordance with 40 CFR §60.40c(a).
- 40 CFR 60 Subparts K; Ka Standards of Performance for Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After June 11, 1973, and Prior to May 19, 1978 (for K); and After May 18, 1978, and Prior to July 23, 1984 (for Ka):

 All tanks at the facility were constructed in 1986.
- 40 CFR 60 Subpart Kb Standards of Performance for Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced After July 23, 1984: All tanks at the facility are below 75 m³ (19,813 gallons) in capacity. Therefore, Subpart Kb is not applicable in accordance with 40 CFR §60.110b(a).
- 40 CFR 60 Subpart KKK Standards of Performance for Equipment Leaks of VOC From Onshore Natural Gas Processing Plants for Which Construction, Reconstruction, or Modification Commenced After January 20, 1984, and on or Before August 23, 2011: This compressor station is not a natural gas processing plant and does not have a "process unit" as defined in 40 CFR §60.631.
- 40 CFR 60 Subpart IIII Standards of Performance for Stationary Compression Ignition Internal Combustion Engines: There are no compression ignition engines at this facility.
- 40 CFR 60 Subpart JJJJ Standards of Performance for Stationary Spark Ignition Internal Combustion Engines: All engines at the facility were constructed, reconstructed, or modified prior to June 12, 2006.
- 40 CFR 60 Subpart OOOO Standards of Performance for Crude Oil and Natural Gas Production, Transmission and Distribution for which Construction, Modification or Reconstruction Commenced after August 23, 2011, and on or before September 18, 2015: There are no affected facilities located at the Horsemill Compressor Station that commenced construction, modification, or reconstruction after August 23, 2011, and on or before September 18, 2015.
- 40 CFR 60 Subpart OOOOa Standards of Performance for Crude Oil and Natural Gas Facilities for which Construction, Modification or Reconstruction Commenced After September 18, 2015:

 There are no affected facilities located at the Horsemill Compressor Station that commenced construction, modification, or reconstruction after September 18, 2015.

- 40 CFR 63 Subpart HHH National Emission Standards for Hazardous Air Pollutants from Natural gas Transmission and Storage Facilities: This subpart does not apply to the facility since it is not defined as a major source of HAPs.
- 40 CFR 63 Subpart DDDDD National Emission Standards for Hazardous Air Pollutants for Major Sources: Industrial, Commercial, and Institutional Boilers and Process Heaters: This subpart does not apply to the facility since it is not defined as a major source of HAPs.
- 40 CFR 63 Subpart JJJJJJ National Emission Standards for Hazardous Air Pollutants for Industrial, Commercial, and Institutional Boilers Area Sources: The reboiler (RBV-1) is a gas-fired "process heater" and therefore excluded from the definition of "boiler" pursuant to §63.11237.
- 40 CFR 64 Compliance Assurance Monitoring (CAM): There are no add-on controls at this facility; therefore, in accordance with 40CFR §64.2(a) CAM is not applicable to this facility.

3.8. Emergency Operating Scenario

- 3.8.1. For emergency situations which interrupt the critical supply of natural gas to the public, and which pose a life threatening circumstance to the customer, the permittee is allowed to temporarily replace failed engine(s) as long as all of the following conditions are met:
 - a. The replacement engine(s) is only allowed to operate until repair of the failed engine(s) is complete, but under no circumstance may the replacement engine(s) operate in excess of sixty (60) days;
 - b. Both the replacement engine(s) and the repaired failed engine(s) shall not operate at the same time with the exception of any necessary testing of the repaired engine(s) and this testing may not exceed five (5) hours;
 - c. Potential hourly emissions from the replacement engine(s) are less than or equal to the potential hourly emissions from the engine(s) being replaced;
 - d. Credible performance emission test data verifying the emission rates associated with the operation of the substitute engine shall be submitted to the Director within five (5) days;
 - e. The permittee must provide written notification to the Director within five (5) days of the replacement. This notification must contain:
 - i. Information to support the claim of life threatening circumstances to justify applicability of this emergency provision;
 - ii. Identification of the engine(s) being temporarily replaced;
 - iii. The design parameters of the replacement engine(s) including, but not limited to, the design horsepower and emission factors;
 - iv. Projected duration of the replacement engine(s); and
 - v. The appropriate certification by a responsible official.

4.0 Dehydration and Reboiler [emission point ID(s): 001-04 and 001-05]

4.1. Limitations and Standards

4.1.1. Maximum Throughput Limitation. - The maximum wet natural gas throughput to the glycol dehydration unit/still column (NATCO Model 90-200) shall not exceed 30 mmscf/day. Compliance with the Maximum Throughput Limitation shall be determined by recording daily wet natural gas throughput to the glycol dehydration unit.

[45CSR13, R13-2808, 5.1.1, 45CSR§30-5.1.c]

4.1.2. Maximum emissions from the Glycol Regenerator Still Vent (RSV-1) shall not exceed the following potential to emit (pounds per hour and tons per year):

Pollutant	Hourly Emissions (lb/hr)	Annual Emissions (ton/yr)
Volatile Organic Compounds	10.42	45.67
Benzene	0.197	0.86
Ethylbenzene	0.572	2.51
Toluene	0.696	3.05
Xylenes	0.820	3.59
n-Hexane	0.181	0.79

[45CSR13, R13-2808, 5.1.2.]

- 4.1.3. For purposes of determining potential HAP emissions at production-related facilities, the methods specified in 40 CFR 63, Subpart HH (i.e. excluding compressor engines from HAP PTE) shall be used. [45CSR13, R13-2808, 5.1.3.]
- 4.1.4. No person shall cause, suffer, allow or permit emission of smoke and/or particulate matter into the open air from any fuel burning unit which is greater than ten (10) percent opacity based on a six minute block average. [45CSR§2-3.1]

4.2. Monitoring Requirements

4.2.1. In order to demonstrate compliance with Condition 4.1.2, the permittee shall have the option of using GRI-GlyCalc Version 3.0 or higher to estimate emissions from the glycol dehydration unit/still column (NATCO Model 90-200). However, to exercise this option the glycol dehydration system must be accurately defined by monitoring and recording actual operating parameters associated with the emission unit. The following parameters shall be measured periodically in order to define annual average values, or if monitoring is not practical some parameters may be assigned default values as listed below. For the purposes of this condition, the term *periodically* shall be interpreted as sufficient enough to reflect annual variation and therefore, this term is an operating parameter and site dependent.

With the exception of wet gas composition, which shall be measured in accordance with Condition 4.3.1., the permittee shall monitor and record bi-monthly the actual operating parameters listed below. These are required to be measured or assumed to equal the default values listed below in order to satisfy this monitoring requirement when using the Gas Analysis and Process Data, GRI-GLYCalc emission modeling method:

- Natural Gas Flowrate:
 - o number of days operated per year.
 - o annual daily average (MMscf/day), and
 - o maximum design capacity (MMscf/day)
- Absorber temperature and pressure
- Lean glycol circulation rate
- Glycol pump type
- Flash tank temperature and pressure, if applicable
- Stripping Gas flow rate, if applicable
- Wet gas composition (upstream of the absorber dehydration column) Sampled in accordance with GPA method 2166 and analyzed consistent with GPA extended method 2286 as well as the procedures presented in the GRI-GLYCalc Technical Reference User Manual and Handbook V4.
- Wet gas water content shall be measured with a dew point meter at a location prior to the contactor column, but after the last liquid knock out pot.
- Dry gas water content shall be measured with a dew point meter at a location after the contactor column.

The following operating parameter(s) may be assigned default values when using GRI-GLYCalc:

 Lean glycol water content if not directly measured may use the default value of 1.5 % water as established by GRI.

[45CSR13, R13-2808, 5.2.1; 45CSR§30-5.1.c]

4.3. Testing Requirements

4.3.1. At least once per calendar year upon issuance of the permit, the permittee shall determine the contents of the wet natural gas stream by analyzing the sample using GPA Method 2286 extended analysis. As specified in the handbook the permittee shall sample the wet gas stream at a location prior to the glycol dehydration column, but after any type of separation device, in accordance with sampling method GPA 2166. The permittee may utilize other equivalent methods provided they are approved in advance by DAQ as part of a testing protocol. If alternative methods are proposed, a test protocol shall be submitted for approval no later than 60 days before the scheduled test date.

[45CSR13, R13-2808, 5.3.1.]

4.4. Recordkeeping Requirements

- 4.4.1. The permittee shall maintain a monthly record of the daily wet natural gas throughput through the glycol dehydration unit to demonstrate compliance with Condition 4.1.1 of this permit.
 - [45CSR13, R13-2808, 5.4.1; 45CSR§30-5.1.c]
- 4.4.2. For the purpose of demonstrating compliance with the limits set forth in Condition 4.1.2, the permittee shall maintain records of the flow rate measurements and wet gas analysis made during the initial compliance determination or subsequent compliance determinations in accordance with Conditions 4.2.1 and 4.3.1. [45CSR13, R13-2808, 5.4.2; 45CSR§30-5.1.c]
- 4.4.3. The permittee shall maintain records of the GLYCalc analysis as required by Condition 4.2.1 of this permit. Said records shall include a printout of the aggregate calculations report, which shall include emissions

reports, equipment reports, and stream reports. The permittee shall maintain bi-monthly records of the input parameters required by Condition 4.2.1.

[45CSR13, R13-2808, 5.4.3.]

4.4.4. Records required under Conditions 4.4.1 – 4.4.3 shall be maintained on site or in a readily accessible off-site location maintained by the permittee. These records shall be readily available to the Director of the Division of Air Quality or his/her duly authorized representative for expeditious inspection and review. Any records submitted to the agency pursuant to a requirement of this permit or upon request by the Director shall be certified by a responsible official.

[45CSR13, R13-2808, 5.4.4.]

4.5. Reporting Requirements

4.5.1. If the results of the compliance determination conducted as required in Conditions 4.2.1 and 4.3.1 predict the emission(s) to be greater than 9.4 tons per year for any single HAP, or a combined total of HAPs greater than 24.4 tons per year, the permittee shall submit such determination and all supporting documentation to the Director within 15 days after making such determination.

[45CSR13, R13-2808, 5.5.1; 45CSR§30-5.1.c]

4.6. Compliance Plan

4.6.1. N/A

5.0 Exemption (Less than 1 ton/year Benzene Exemption Subpart HH)

5.1. Limitations and Standards

5.1.1. To qualify for the less than 1.0 tons/yr actual average emissions of Benzene per glycol dehydration unit exemption of 40 CFR 63 Subpart HH, the permittee shall comply with the limit in Table 1.0.

Table 1.0 Glycol Dehydration Unit

Description	Mg/yr	Tons/Yr
Benzene	< 0.9	< 1.0

[45CSR13, R13-2808, 6.1.1.]

- 5.1.2. To claim less than 1 ton/year of Benzene exemption as stated in Condition 5.1.1 of this permit, the permittee shall adhere to the following:
 - a. The actual average emissions of benzene from the individual still vent of the glycol dehydration unit to the atmosphere shall be less than 1.0 ton per year (0.9 megagram per year). Emissions shall be determined either uncontrolled, or with federally enforceable controls in place.

 [45CSR34, 40 CFR §63.764(e)(1)(ii)]
 - b. The permittee shall determine the actual average benzene emission using the model GRI-GLYCalc™, Version 3.0 or higher, and the procedures presented in the associated GRI-GLYCalc™ Technical Reference Manual. Inputs to the model shall be representative of actual operating conditions of the glycol dehydration unit and may be determined using the procedures documented in the Gas Research Institute (GRI) report entitled "Atmospheric Rich/Lean Method for Determining Glycol Dehydrator Emissions" (CGR-95/0368.1); or

The permittee shall determine an average mass rate of benzene emissions in kilograms per hour through direct measurement using the methods set forth in 40 CFR §63.772(b)(2)(ii). Annual emissions in kilograms per year shall be determined by multiplying the mass rate by the number of hours the unit is operated per year. This result shall be converted to megagrams per year. Permittees with federally enforceable controls are exempt from the requirements to conduct site-specific extended gas analysis.

[45CSR34, 40 CFR §§63.772(b)(2)(i)-(ii)]

c. All records required under Section 5 shall be maintained on site or in a readily accessible off-site location maintained by the permittee for a period of five (5) years. Said records shall be readily available to the Director of the Division of Air Quality or his/her duly authorized representative for expeditious inspection and review. Any records submitted to the agency pursuant to a requirement of this permit or upon request by the Director shall be certified by a responsible official.

[45CSR13, R13-2808, 6.1.2.]

- 5.1.3. 40 CFR §63.760 Applicability and designation of affected source. (Note that the following Section numbers match those of §63.760.)
 - (f) The owner or operator of an affected area source shall achieve compliance with the provisions of 40 CFR 63 Subpart HH by the dates specified in paragraphs (f)(3) through (f)(6) of this section.

(4) The owner or operator of an affected area source, located in an Urban-1 county, as defined in §63.761, the construction or reconstruction of which commences on or after February 6, 1998, shall achieve compliance with the provisions of this subpart immediately upon initial startup or January 3, 2007, whichever date is later.

[45 CSR34, 40 CFR §63.760]

- 5.1.4. 40 CFR §63.764 General Standards (Note that the following Section numbers match those of §63.764.)
 - (d) Except as specified in 40 CFR §63.764(e)(1), the owner or operator of an affected source located at an existing or new area source of HAP emissions shall comply with the applicable standards specified in paragraph (d) of this Condition.
 - (1) Each owner or operator of an area source located within an UA plus offset and UC boundary (as defined in §63.761) shall comply with the provisions specified in paragraphs (d)(1)(i) through (iii) of this Condition.
 - (i) The control requirements for glycol dehydration unit process vents specified in 40 CFR §63.765;
 - (ii) The monitoring requirements specified in 40 CFR §63.773; and
 - (iii) The recordkeeping and reporting requirements specified in 40 CFR §§63.774 and 63.775.
 - (e) Exemptions.
 - (1) The owner or operator is exempt from the requirements of 40 §§63.764(c)(1) and (d) if the criteria listed in 40 CFR §§63.764(e)(1)(i) or (ii) are met, except that the records of the determination of these criteria must be maintained as required in 40 CFR §63.774(d)(1).
 - (ii) The actual average emissions of benzene from the glycol dehydration unit process vent to the atmosphere are less than 0.90 megagram per year, as determined by the procedures specified in 40 CFR §63.772(b)(2) of 40 CFR63 Subpart HH (Condition 5.1.2 of this permit).

[45CSR34, 40 CFR §63.764]

5.1.5. If the annual emissions of benzene from the dehydration unit (RSV-1) for 2009 or any year thereafter equals or exceeds 0.90 megagram per year (1 tpy) as calculated per 40 CFR §63.772(b)(2) (Condition 5.1.2 of this permit), the permittee shall comply with 40 CFR §§63.764(d)(1)(i) through (iii) (Condition 5.1.4 of this permit).

[45CSR§30-12.7.]

- 5.1.6. 40 CFR §63.774 Recordkeeping requirements (Note that the following Section numbers match those of §63.774.)
 - (d)(1) An owner or operator of a glycol dehydration unit that meets the exemption criteria in 40 CFR \$63.764(e)(1)(ii) (Condition 5.1.4) shall maintain the records specified in paragraph 40 CFR \$63.764(d)(1)(ii) for that glycol dehydration unit.

(ii) The actual average benzene emissions (in terms of benzene emissions per year) as determined in accordance with 40 CFR §63.772(b)(2) (Condition 5.1.2).

[45 CSR34, 40 CFR §63.774 (d)(1)]

- 5.2. Monitoring Requirements
 - 5.2.1. Reserved
- 5.3. Testing Requirements
 - 5.3.1. Reserved
- 5.4. Recordkeeping Requirements
 - 5.4.1. Reserved
- 5.5. Reporting Requirements
 - 5.5.1. Reserved
- 5.6. Compliance Plan
 - 5.6.1. N/A

6.0 Compressor Engines #1 and #2 [emission point ID(s): 001-02 and 001-03]

6.1. Limitations and Standards

6.1.1. For the Non-Emergency SI 4SRB Engines, as stated in 40 CFR §63.6603 the permittee must comply with the following requirements from Table 2d for existing stationary RICE located at area sources of HAP emissions:

For each	The permittee must meet the following requirements, except during periods of startup	During periods of startup you must
Non-emergency, non-black start	Change oil and filter every 2,160 hours of operation or annually, whichever comes first; ¹	See Condition 6.2.1.
4SRB remote stationary RICE >500 HP	Inspect spark plugs every 2,160 hours of operation or annually, whichever comes first; and replace as necessary; and	
- 500 III	Inspect all hoses and belts every 2,160 hours of operation or annually, whichever comes first, and replace as necessary.	

¹Sources have the option to utilize an oil analysis program as described in §63.6625(j) in order to extend the specified oil change requirement in Table 2d of 40 CFR 63 Subpart ZZZZ.

[45 CSR34, 40 CFR §§63.6595(a)(1), 63.6603(a), and Table 2d - Item 11]

6.1.2. The permittee must evaluate the "remote" status of each compressor engine #1, and #2 every 12 months. Records of the initial and annual evaluation of the status of the engines must be kept. If the evaluation indicates that the compressor engine no longer meets the definition of remote stationary RICE in 40 CFR §63.6675, the permittee must comply with all of the requirements for existing non-emergency SI 4SRB stationary RICE with a site rating of more than 500 HP located at area sources of HAP that are not remote stationary RICE within 1 year of the evaluation.

[45 CSR34, 40 CFR §63.6603(f)]

- 6.1.3. The permittee shall comply with the following requirements:
 - a. The permittee must be in compliance with the operating limitations in 40 CFR 63 Subpart ZZZZ that apply to the permittee at all times.
 - b. At all times the permittee must operate and maintain any affected source, including associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions. The general duty to minimize emissions does not require the permittee to make any further efforts to reduce emissions if levels required by this standard have been achieved. Determination of whether such operation and maintenance procedures are being used will be based on information available to the Administrator which may include, but is not limited to, monitoring results, review of operation and maintenance procedures, review of operation and maintenance records, and inspection of the source.

[45 CSR34, 40 CFR §63.6605]

6.1.4. The permittee must demonstrate continuous compliance with each emission limitation and operating limitation in Table 2d to 40 CFR 63, Subpart ZZZZ that apply to the permittee according to methods specified in Table 6 to 40 CFR 63, Subpart ZZZZ.

- a. Table 6 states that for work or management practices the permittee shall operate and maintain the stationary RICE according to the manufacturer's emission related operation and maintenance instructions; or
- b. Develop and follow your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions.

[45 CSR34, 40 CFR §63.6640(a) and Table 6 - Item 9]

6.1.5. The permittee shall comply with all General Provisions which apply according to Table 8 to 40 CFR, Part 63, Subpart ZZZZ except for §§63.7(b) and (c), 63.8(e), (f)(4), and (f)(6), and 63.9(b)-(e), (g) and (h) which do not apply per 40 CFR §63.6645(a)(5).

[45 CSR34, 40 CFR §§63.6665 and 63.6645(a)(5)]

6.2. Monitoring Requirements

6.2.1. If you operate an existing stationary engine, you must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the emission standards applicable to all times other than startup in Table 2d to 40 CFR 63 Subpart ZZZZ apply.

[45 CSR34, 40 CFR §63.6625(h) and Table 2d]

6.2.2. If you own or operate a stationary SI engine that is subject to the work, operation or management practices in item 11 of Table 2d to 40 CFR 63 Subpart ZZZZ, you have the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Table 2d to 40 CFR 63 Subpart ZZZZ. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2d to 40 CFR 63 Subpart ZZZZ. The analysis program must at a minimum analyze the following three parameters: Total Acid Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Acid Number increases by more than 3.0 milligrams of potassium hydroxide (KOH) per gram from Total Acid Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 business days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 business days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine.

[45 CSR34, 40 CFR §63.6625(j)]

6.3. Testing Requirements

6.3.1. Reserved.

6.4. Recordkeeping Requirements

6.4.1. The Permittee shall keep the following records:

- a. A copy of each notification and report submitted to comply with this subpart, including all documentation supporting any Initial Notification or Notification of Compliance Status submitted, according to the requirement in 40 CFR §63.10(b)(2)(xiv).
- b. Records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment.
- c. Records of all required maintenance performed on the air pollution control and monitoring equipment.
- d. Records of actions taken during periods of malfunction to minimize emissions in accordance with 40 CFR §63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation.

[45 CSR34, 40 CFR §§63.6655(a)(1), (2), (4), and (5)]

- 6.4.2. Records of the monitoring required by Table 6 of subpart ZZZZ, item #9 (Condition 6.1.4.) shall be kept to show continuous compliance with each emission or operating limitation that applies to you.

 [45 CSR34, 40CFR §§63.6655(d)]
- 6.4.3. The permittee must keep records of the maintenance conducted on each stationary RICE in order to demonstrate that the permittee operated and maintained each stationary RICE and after-treatment control device (if any) according to the permittee's own maintenance plan.
 [45 CSR34, 40 CFR §63.6655(e)]
- 6.4.4. The permittee shall comply with the following recordkeeping requirements:
 - a. Your records must be in a form suitable and readily available for expeditious review according to §63.10(b)(1). (See Condition 3.4.2.)
 - b. As specified in §63.10(b)(1), you must keep each record for 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record.
 - c. You must keep each record readily accessible in hard copy or electronic form for at least 5 years after the date of each occurrence, measurement, maintenance, corrective action, report, or record, according to §63.10(b)(1).

[45 CSR34, 40 CFR §§63.6660 and 63.10(b)(1)]

6.5. Reporting Requirements

- 6.5.1. The permittee must report each instance in which you did not meet each operating limitation in Table 2d to 40 CFR 63, Subpart ZZZZ that apply. These instances are deviations from the emission and operating limitations. These deviations must be reported according to the requirements in 40 CFR §63.6650.

 [45 CSR34, 40 CFR §63.6640(b)]
 - [15 0515 1, 10 0212 305100 10(5)]
- 6.5.2. The permittee must report each instance in which the applicable requirements in Table 8 to 40 CFR 63, Subpart ZZZZ were not met.

[45 CSR34, 40 CFR §63.6640(e)]

6.5.3. The permittee must report all deviations as defined in 40 CFR 63, Subpart ZZZZ in the semiannual monitoring report required by 40 CFR 70.6 (a)(3)(iii)(A) or 40 CFR 71.6(a)(3)(iii)(A). [45 CSR34, 40 CFR §63.6650(f)]

6.6. Compliance Plan

6.6.1. N/A